

## **DECLARATION OF PERFORMANCE**

according to Annex III of the Regulation (EU) Nr. 305/2011 (Construction Products Regulation)

Nr. Bistal-DoP-003-13/EN

1.Product type: Bistal bed joint reinforcement of welded steel wire meshwork,

type Bi 40 ob - Quality 700/18

2. Type identification of the

construction product: Type and article number displayed on the packaging

3.Intended use of the product: Welded wire meshwork - ladder type, bed joint reinforcement in masonry for

structural applications.

4.Manufacturer: Bistål AB i västervik, Fridkullagatan 5, SE- 593 62 Västervik

6.System of assessment and

verification of performance: System 3

7. Harmonized standard: EN-845-3:2013

Notified body No. 0402, SP Technical Research Institute of Sweden has performed initial type testing (ITT) of the product according to the standard.

9.Declared performance:

**Dimensions Limit deviations** 4 000 mm +/- 1,5 % Length (I) +/- 5 mm Width (a) 18 mm Profile height (t) 4,0 mm +/- 0,4 mm Wire size (c) 4,0 mm +/- 0,1 mm Wire size (d) +/- 0,1 mm 3x4 mm Pitch of wires (b) 95 mm +/-3%

Essential characteristics Performance data Harmonized technical specification

Coating reference	NPD	Table 1, EN-845-3
Shear load capacity	4,8 kN	EN-845-3 + FPC
Characteristic yield strength of wires	690 MPa	EN-845-3 – ITT by notified body
Bond strength	3,08 kN	EN-845-3 – ITT by notified body
Anchorage length	300 mm or 3 cross wires	EN 845-3
Ductility class	High < 1,08	Table 4, EN-845-3

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Västervik July 1, 2013

Stefan Stein Stefan Stein