

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) Nr. 305/2011 (Construction Products Regulation)

Nr. Joma - DoP - 008-13/EN

| 1.Product type: | Joma wall-tie Nr. 15 is an asymmetrical thrust nail type, made of 4,0 or 4,4 mm stainless steel wire. | |
|---|---|------------------------------------|
| 2.Type identification of the construction product: | Type and article number displayed on the packaging | |
| 3.Intended use of the product: | Designed for connecting masonry walls to timber structures | |
| 4.Manufacturer: | Joma AB, Målskog, SE -33591 Gnosjö, Sweden | |
| 6.System of assessment and verification of performance: | System 3 | |
| 7.Harmonised standard: | EN-845-1:2013 Notified body No. 1235, Teknologisk Institut, DK-8000, Århus has performed initial type testing of the product according to the standard. | |
| 9.Declared performance: | Dimensions mm Length mm 75 100 125 145 175 200 225 250 300 | |
| Essential characteristics | Performance data | Harmonized technical specification |
| Tensile load capacity | Min. 2,3 kN (M2,5 mortar) | EN-845-1 |
| Compresion load capacity | Design according o EC 3 and EC 6 | |
| Water crossing | Resistant | EN-845-1 |
| Material coating | Austenitic stainless steel, ref 1 or 3 | · · · |
| Corrosion class | Class MX 4 | Eurocode 6 |
| Minimum embedment length | 40 mm | EN-845-1 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Gnosjö July 1, 2013

Yngve Josefsson Technical and Quality Manager