

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) Nr. 305/2011 (Construction Products Regulation)

Nr. Joma – DoP – 015 -13/EN

- 1.Product type: **Joma Brick-rail with associated U-shaped wall tie made of stainless steel**
- 2.Type identification of the construction product: **Type and article number displayed on the packaging**
- 3.Intended use of the product: **Designed to anchor cavity brick walls to sheet metal studs and insulation panels with thin sheet metal walls.**
- 4.Manufacturer: **Joma AB, Målskog, SE -33591 Gnosjö, Sweden**
- 6.System of assessment and verification of performance: **System 3**
- 7.Harmonised standard: **EN-845-1:2013**
Notified body No. 1235, Teknologisk Institut, DK-8000, Århus has performed initial type testing (ITT) of the product according to the standard.
- 9.Declared performance: **Dimensions mm**
Length rail: 2 400 mm
Wall tie: 4,0 x 100 mm

Essential characteristics	Performance data	Harmonized technical specification
Tensile load capacity	Min. 1,12 kN	EN-845-1 + ITT av anmält organ
Compression load capacity	Design according to EC 3 and EC 6	
Water crossing	NPD	
Material coating	Austenitic stainless steel, ref 1 or 3	EN-845-1, annex A, Tabell A1
Corrosion class	Class MX 4	Eurocode 6
Minimum embedment length	40 mm (brick wall)	EN-845-1

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer by:

Gnosjö July 1, 2013



Yngve Josefsson
Technical and Quality Manager